

**Specifications :**



Model		<b>DCA-25ESK</b>	
<b>ALTERNATOR</b>			
Frequency	Hz	50	60
Output Rating (kVA)	Continuous	20	25
	Standby	22	27.5
No. of Phases		3-Phase , 4-Wire	
Rated Voltage	V	Dual Voltage	
Power Factor		0.8 (Lagging)	
Voltage Regulation		Within ±0.5	
Excitation		Brushless, Rotating Exciter (with A.V.R.)	
Insulation		Class F	
<b>ENGINE</b>			
Maker & Model		Kubota V2203-KB	
Type		Inlined, Swirl Chambered	
Output Rating	PS / rpm	25 / 1500	32.2 / 1800
	kW / min <sup>-1</sup>	18.4 / 1500	23.7 / 1800
No. of Cylinders - Bore x Stroke		mm 4 - 87 x 92.4	
Piston Displacement		L 2.197	
Fuel		ASTM No.2 Diesel Fuel or Equivalent	
Fuel Consumption	L / h	3.9	4.9
Lube Oil Sump Capacity		L 7.6	
Coolant Capacity		L 7.9	
Battery x Quantity		80D26R x1	
Fuel Tank Capacity		L 62	
<b>UNIT</b>			
Dimensions L x W x H		mm 1540 x 650 x 900	
Dry Weight		kg 591	
<b>SOUND LEVEL</b>			
7m dB(A) 1500/1800 rpm (min <sup>-1</sup> )		62	64

**Denyo**

**Soundproof**

**Diesel Generator**

**DCA-25ESK**

