

REVERSIBLE VIBRATORY PLATE

BPU 2540 (PETROL)



APPLICATIONS

- Compacting paving stones, horticulture & landscaping, & maintenance of roads, paths & parking lots
- Suited for compaction of sidewalks, trenches & other confined areas

OPERATING DATA

OPERATING WEIGHT	145 kg
CENTRIFUGAL FORCE	25 kN
BASE PLATE SIZE (W x L)	400 x 703 mm
BASE PLATE THICKNESS	10 mm
HEIGHT (without GUIDE HANDLE)	647 mm
OPERATING WIDTH	400 mm
FREQUENCY	90 Hz
ADVANCE TRAVEL MAX. *	21 m/min
SURFACE CAPACITY MAX. *	504 m ² /h

* Depending on soil & environmental factors

ENGINE / MOTOR

ENGINE / MOTOR TYPE	GX 160
ENGINE / MOTOR MANUFACTURER	Honda
ENGINE / MOTOR	Air-cooled single-cylinder, four-cycle gasoline engine
DISPLACEMENT	163 cm ³
ENGINE PERFORMANCE MAX.	4 kW (DIN ISO 3046)
AT rpm	3600 rpm
FUEL CONSUMPTION	0.8 l/h
FUEL TANK CAPACITY	3.7 l
POWER TRANSMISSION	From drive motor via automatic centrifugal belt drive direct to exciter