

# REVERSIBLE VIBRATORY PLATE DPU 3060 (DIESEL)



**APPLICATIONS**

- Compacting paving stones, horticulture & landscaping, & maintenance of roads, paths & parking lots
- Suited for compaction of sidewalks, trenches & other confined ground spaces

**OPERATING DATA**

OPERATING WEIGHT	190 kg
CENTRIFUGAL FORCE	30 kN
BASE PLATE THICKNESS	10 mm
HEIGHT	1101 mm
OPERATING WIDTH	600 mm
FREQUENCY	90 Hz
ADVANCE TRAVEL MAX. *	18 m/min
SURFACE CAPACITY MAX. *	648 m <sup>2</sup> /h

\* Depending on soil & environmental factors

**ENGINE / MOTOR**

ENGINE / MOTOR TYPE	1B30
ENGINE / MOTOR MANUFACTURER	Hatz
ENGINE / MOTOR	Air-cooled, single-cylinder, 4-stroke diesel engine (recoil start)
DISPLACEMENT	347 cm <sup>3</sup>
ENGINE PERFORMANCE MAX.	5.4 kW (DIN ISO 3046)
AT rpm	3600 rpm
FUEL CONSUMPTION	0.6 l/h
FUEL TANK CAPACITY	5.0 l
POWER TRANSMISSION	From drive motor via centrifugal clutch & V-belt direct to exciter