

# REVERSIBLE VIBRATORY PLATE

**DPU 3760 (DIESEL)**



## APPLICATIONS

- Compacting paving stones, horticulture & landscaping, & maintenance of roads, paths & parking lots
- Suited for compaction of sidewalks, trenches & other confined ground spaces

## OPERATING DATA

OPERATING WEIGHT	274 kg
CENTRIFUGAL FORCE	37 kN
BASE PLATE SIZE (W x L)	600 x 703 mm
BASE PLATE THICKNESS	10 mm
HEIGHT (without GUIDE HANDLE)	771 mm
OPERATING WIDTH	600 mm
FREQUENCY	90 Hz
ADVANCE TRAVEL MAX. *	26 m/min
SURFACE CAPACITY MAX. *	936 m <sup>2</sup> /h

\* Depending on soil & environmental factors

## ENGINE / MOTOR

ENGINE / MOTOR TYPE	1B30
ENGINE / MOTOR MANUFACTURER	Hatz
ENGINE / MOTOR	Air-cooled, single-cylinder, 4-cycle diesel engine
DISPLACEMENT	347 cm <sup>3</sup>
ENGINE PERFORMANCE MAX.	5.4 kW (DIN ISO 3046)
AT rpm	3600 rpm
FUEL CONSUMPTION	0.6 l/h
FUEL TANK CAPACITY	5.0 l
POWER TRANSMISSION	From drive motor via centrifugal